

POLISH HONE RESTORE

or remove a scratch...

FOR COUNTERTOPS:
"This tool has been
a life saver. It is so
simple to use and
it works."

FOR MONUMENTS:
"It works better
than advertised.
It sped our
process up by
at least 50%"

"That thing
is pretty
amazing!"

VT: 800.396.8049
PA: 888.278.8383
MN: 800.789.0815
GA: 888.283.5863
TX: 844.883.4108
IL: 815.847.0080
milessupply.com



Recommended for your Patch Kit: The PadHead™ polishing & grinding head 7" Low-Profile Model II, a Wet Polisher, a complete set of 3" wet diamond pads, and backer & buffing pad.

Patch-the-Scratch Kit

Featuring our patented

PadHead™

polishing & grinding head



Steps for Scratch Removal

For first timers, practice on scrap pieces

1. In the smallest possible space, use 50g, 100g, or 200g pads, working the scratched area until the scratch is removed.
2. At the 400g stage, expand the radial working area about 1" to 1½". Check for a consistent diamond scratch pattern relative to the grit used.
3. Repeat step 2 for 800g, 1500g, and 3000g expanding the working area 1" or so at a time.

For Engineered Stone – you should be complete at either the 1500g or 3000g stage, when color and match is achieved.
For Granite – After the 3000 grit, swap out the PadHead™ with a rigid backer and felt buff pad.
Create a slurry using Miles Polishing Powder on the area being worked. Then shut off water... Work the Miles Polishing powder into the stone until a final matching polish is achieved.



Air or Electric Polisher