

129Y

DOUBLE LINER MEDIUM TACK MEDIA BLAST STENCIL - MACHINE CUT

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

High quality, durable stencil coated with an advanced, medium tack, rubber-based pressure-sensitive adhesive protected by a clear PET liner. Designed for precision cutting IBM® pattern cutters. The slot-hole pattern will also accurately track through Gerber® 15" and friction-fed plotters. #129Y contains a yellow inner sheet of polyester which retains cut designs during liner removal. This same construction is found in #123, #124, and #154 stencil products. Recommended for single-process media blast carving of granite or marble.

PRODUCT APPLICATIONS

The 30" will not work on large pin computer cutters. Replaces #123 in IBM® plotter applications.

STANDARD SIZES

15" x 10 yards, 25" x 10 yards,
25" x 20 yards, 30" x 10 yards

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	47 (1.19mm)
Total Thickness w/o Liner (mil) PSTC-133	45 (1.14mm)
Tensile Strength (lbs/in) PSTC-131	5 (21.9 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	19 (5.2 N/25mm)
Elongation (% at break) PSTC-131	300
Punch	15" and 30" Friction Fed; 25" and 30" Sprocket Fed 1/2" OC
Liner Color	(Inner) Yellow (Outer) Clear
Recommended Filler	#223



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/20