

# 124

## COMPUTER STENCIL

### DESCRIPTION

High quality, durable stencil construction with medium tack, rubber-based, pressure sensitive adhesive protected by a light blue liner. Designed for precision cutting in slot-hole pattern cutters. The tractor-fed holes are punched through both rubber and liner. The 15" width will track and process on both IBM® and Gerber® pattern cutters. The 30" width will fit only Gerber® #750 plotter machines. The inner sheet of polyester maintains alignment of cut designs during transfer from plotter to stone. #124 is designed and recommended for single-process shaped carving on polished granite or marble.

### PRODUCT APPLICATIONS

For optimum performance, use with #223 or #333 Stencil Fillers. 30" widths will track only on large pin computer cutters. Replaces #123 in Gerber® plotter applications.

### STANDARD SIZES:

- 15" x 10 yards
- 30" x 10 yards
- 30" x 20 yards



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/14

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Adhesive</b>	Medium Tack / Rubber
<b>Total Thickness</b> (mil) PSTC-133	48 (1.22mm)
<b>Tensile Strength</b> (lbs/in) PSTC-131	5 (21.9 N/25mm)
<b>180° Adhesion to Steel</b> (oz/in) PSTC-101	25 (6.8 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	300

